



S SCLC Internal turning (KAPR 95°)		R	L	DMIN	DCON	WF	LF	GAMO	KG	MIID

	Model	R	L	DMIN	DCON	WF	LF	GAMO	KG	MIID
06	NT-S08H-SCLC%/06	●	●	10	8	5	100	13°		CC□0602
	NT-S10K-SCLC%/06	●	●	12	10	6	125	12°		
	NT-S12M-SCLC%/06	●	●	14	12	7	150	9°		
	NT-S16Q-SCLC%/06	●	●	18	16	9	180	7°		
09	NT-S12M-SCLC%/09	●	●	14	12	7	150	13°		CC□09T3
	NT-S16Q-SCLC%/09	●	●	18	16	9	180	9°		
	NT-S20R-SCLC%/09	●	●	22	20	11	200	5°		
12	NT-S20R-SCLC%/12	●	●	25	20	13	200	8°		CC□1204
	NT-S25R-SCLC%/12	●	●	32	25	17	200	8°		
	NT-S32S-SCLC%/12S	●	●	40	32	22	250	6°		CC□1204
	NT-S40T-SCLC%/12S	●	●	50	40	27	300	4°		

● stock standard



Model	SHIM	SHIM SCREW	SHIM WRENCH	INSERT SCREW	INSERT WRENCH
NT-S08H-SCLC%/06				NT-ST006	NT-FT07
NT-S10K-SCLC%/06	-	-	-	NT-ST010	
NT-S12M-SCLC%/06	-	-	-	NT-ST010	
NT-S16Q-SCLC%/06					
NT-S12M-SCLC%/09				NT-ST025	NT-FT15
NT-S16Q-SCLC%/09	-	-	-	NT-ST030	
NT-S20R-SCLC%/09					
NT-S20R-SCLC%/12				NT-ST050	NT-FT15
NT-S25R-SCLC%/12	-	-	-	NT-ST050	
NT-S32S-SCLC%/12S	NT-SH001	NT-SR001	NT-WR040	NT-ST007	NT-FT15
NT-S40T-SCLC%/12S					



MIID	CARBIDE	PCBN	CERAMIC	DIAMOND
CC□0602	page 8	page 39	-	page 70
CC□09T3	page 8	page 39	page 56	page 70
CC□1204	page 8	-	page 56	page 70

TURNING
THREADING
GROOVING
MILLING
DRILLING
ACCESSORIES