



S SDUC Internal turning (KAPR 93°)		R	L	DMIN	DCON	WF	LF	GAMO	KG	MIID

07	NT-S10M-SDUC%/07	●	●	13	10	7	150	10°	DC□□0702
	NT-S12M-SDUC%/07	●	●	16	12	9	150	8°	
	NT-S16Q-SDUC%/07	●	●	20	16	11	180	6°	
	NT-S20R-SDUC%/07	●	●	25	20	13	200	5°	
11	NT-S16Q-SDUC%/11	●	●	20	16	11	180	7°	DC□□11T3
	NT-S20R-SDUC%/11	●	●	25	20	13	200	8°	
	NT-S25R-SDUC%/11	●	●	32	25	17	200	4°	
	NT-S32S-SDUC%/11	●	●	39	32	22	250	4°	
	NT-S40T-SDUC%/11	●	●	50	40	24	300	2°	

● stock standard

Spare Parts	INSERT SCREW	INSERT WRENCH

NT-S10M-SDUC%/07	NT-ST010	NT-FT07
NT-S12M-SDUC%/07		
NT-S16Q-SDUC%/07		
NT-S20R-SDUC%/07		
NT-S16Q-SDUC%/11	NT-ST035	NT-FT15
NT-S20R-SDUC%/11		
NT-S25R-SDUC%/11		
NT-S32S-SDUC%/11		
NT-S40T-SDUC%/11		

Inserts	CARBIDE	PCBN	CERAMIC	DIAMOND

DC□□0702	page 14	page 42	-	page 73
DC□□11T3	page 14	page 42	-	page 73

TURNING

THREADING

GROOVING

MILLING

DRILLING

ACCESSORIES